

PERFORMANCE SPECIFICATIONS

Satellite Signals Tracked Simultaneously¹

Channels.....	1408/800+(optional)
GPS.....	L1C/A, L1C, L2P(Y), L2C, L5
BeiDou.....	B1I, B2I, B3I, B1C, B2a, B2b*
GLONASS.....	L1, L2, L3
Galileo.....	E1, E5A, E5, AltBOC, E5B, E6
IRNSS.....	L5
SBAS.....	L1C/A, L5(QZSS, WAAS, MSAS, GAGAN)
QZSS.....	L1, L2, L5, L6*

POSITIONING PERFORMANCE²

High-Precision Static

Horizontal.....	2.5 mm + 0.1 ppm RMS
Vertical.....	3.5 mm + 0.4 ppm RMS

Static and Fast Static:

Horizontal.....	2.5 mm + 0.5 ppm RMS
Vertical.....	5 mm + 0.5 ppm RMS

Post Processing Kinematic (PPK / Stop & Go)

Horizontal.....	8mm+1ppm RMS
Vertical.....	15mm+1ppm RMS

Initialization time..... Typically 10 min for base and 5 min for rover
 Initialization reliability..... Typically > 99.9%

Code Differential GNSS Positioning

Horizontal.....	25cm+1ppm RMS
Vertical.....	50cm+1ppm RMS
SBAS.....	0.5m

Real Time Kinematic (RTK)

Single Baseline

Horizontal.....	8mm+1ppm RMS
Vertical.....	15mm+1ppm RMS

Network RTK(VRS,FKP,MAC)

Horizontal.....	8mm+0.5ppm RMS
Vertical.....	15mm+0.5ppm RMS
Initialization time.....	Typically 2-10s
Initialization reliability.....	Typically > 99.99%

Provides RTK measurements even during differential signal interruptions

Hi-Fix⁵

Horizontal.....	RTK+10mm / minute RMS
Vertical.....	RTK+20mm / minute RMS

Time to first Fix

Cold start.....	< 45 s
Hot start.....	< 30 s
Signal re-acquisition.....	< 2 s

Image Accuracy

Stakeout.....	Typically 2cm
Image Measurement.....	2cm~4cm

Tilt Survey Performance³

Additional horizontal pole-tilt uncertainty typically less than 8mm+0.7mm/°tilt(2.5cm accuracy in the inclination of 60°)

HARDWARE

Physical

Dimensions (W x H).....	130mm×79mm
Weight.....	lighter than 0.97kg (2.14lb) within internal battery
Operation temperature.....	-40°C~+75°C (-40°F~+167°F)
Storage temperature.....	-55°C~+85°C (-67°F~+185°F)
Temperature control.....	Auto-adjust the working power to maintain the temperature
Humidity.....	100%, non-condensing
Water/dustproof.....	IP68 dustproof, protected from temporary immersion to depth of 1.0m (3.28ft)

Shock and vibration.....	MIL-STD-810G, 514.6
Anti-salt spray.....	MIL-STD-810G, 509.4, 96h
Free fall.....	MIL-STD-810G, 516.6, designed to survive a 2m(6.56ft) natural fall onto concrete

Charging

Charging:using standard smartphone chargers or external power banks
 (Support 5V 2.8A Type-C USB external charging)

Control Panel

Physical button.....	1
LED Lights.....	Satellite lights, signal lights, power lights

Camera

Pixel.....	2MP & 5MP
Support real scene stakeout, image measurement, working distance 2~15m	

Internal Battery⁴

7.2V, 6900mAh Built-in lithium-ion battery.
 RTK rover(UHF/Cellular) for 15 hours.
 Power indicator embedded.
 Quick charge within 3.5 hours.

I/O Interface

Bluetooth 4.0/2.1+ EDR, 2.4 GHz. USB type C interface; SMA interface;
 Nano SIM card slot
 Near Field Communication(NFC)

Communication

Network Communication

Full band support for cellular mobile network(LTE, WCDMA, EDGE, GPRS, GSM).
 2.4GHz Wi-Fi, supports the standard protocol 802.11 b/g/n. Network RTK(in CORS)
 range is 20-50km.

Internal UHF Transceiver Radio

Frequency..... 410~470MHz
 Transmitting power..... 0.5W / 1W / 2W adjustable Hi-Target Advanced Radio
 Supports protocols: HI-TARGET, TRIMTALK450S, TRIMMARK III, SATEL-3AS, TRANSEOT, etc.
 Working Range..... Typically 3~5km, optimal 5~8km
 Channels..... 116

SYSTEM CONFIGURATION

System

Data storage..... Circulating 8GB Internal storage
 Record GNS and RINEX format simultaneously

Data Formats

1Hz positioning output, up to 20Hz. RTCM2.X, RTCM3.X .
 Navigation outputs ASCII: NMEA-0183

[1]BDS B2b, GALILEO E6, QZSS L6, IRNSS L5 can be provided by firmware upgrade. BDS B2b is optional for 1408 channels.

[2]The measurement accuracy, precision, reliability and initialization time depend on various factors, including tilt angle, number of satellites, geometric distribution, observation time, atmospheric conditions and multi-path validation, etc. The data are derived under normal conditions.

[3]Irregular operations such as rapid rotation and high-intensity vibration may affect the inertial navigation accuracy.

[4]The battery operating time is related to the operating environment, operating temperature and battery life

[5]Accuracies are dependent on GNSS satellite availability. Hi-Fix Positioning ends after 5 minutes without differential data.Hi-Fix is not available in all regions, check with your local sales representative for more information.

Descriptions and Specifications are subject to change without notice



AUTHORIZED DISTRIBUTION PARTNER

22S109

Hi-Target Surveying Instrument Co., Ltd.

Address: Building 13, Tian'An Technology Zone, No. 555, Panyu North Rd., Panyu District, Guangzhou, China (511400)
 TEL: +86-20-2288 3944 E-mail: info@hi-target.com.cn www.hi-target.com.cn

Vision RTK

VENI, VIDI, VICI

